



También disponible con casquillo cónico

Also available with conical bushing

Acoflex con Polea de freno. Serie AP**Acoflex with Pulley Brake. AP Series**

Mod. AP	A4P-250	A5P-315	A6P-315	A6P-400	A7P-500	A7P-630	A8P-630	A8P-710	A9P-630	A9P-710	A10P-710	
Par Nominal [Nm] Nominal Torque	400	1000	2000	2000	4000	4000	7500	7500	12500	12500	25000	
Par Max [Nm] Max Torque	1000	2500	4000	4000	8000	8000	15000	15000	25000	25000	40000	
Momento de Inercia [kgm²] Moment of Inertia	0.164	0.980	1.355	3.254	5.201	10.453	19.328	20.758	21.651	22.829	25.727	
Diametros [mm] Diameters	A	176	225	267	267	307	307	369	369	432	432	532
	B	110	140	180	180	205	205	242	220	280	280	330
	C	250	315	315	400	500	630	630	710	630	710	710
	Ø d Max	65	85	110	110	130	130	150	150	180	180	210
Longitudes [mm] Lengths	L	177	213	257	257	307	307	378	378	418	418	470
	M	61	75	92	92	113	113	144	144	158	158	180
	N	3.5	3.5	3.5	3.5	4	4	5	5	5	5	6
	S	15	10	25	20	25	5	10	5	20	10	25
	T	95	118	118	150	190	236	236	265	236	265	265
Ref. Guarnición Insert Ref.	G4	G5	G6	G6	G7	G7	G8	G8	G9	G9	G10	